Claims ~~for the Patent~~

1.   ~~(Amended):~~____Communication model characterized in that whether reachability to ~~a~~ the destination communication node ~~(4100)~~ is true or false is determined by comparing the mapped image (at mapping announcement system) of ~~a~~ the pair consisting of a static identifier and ~~dynamically assigned network~~ dynamic address that indicate the destination communication node ~~(4100) in a mapping notification system (1000)~~ and the real image (at destination communication node) of the pair consisting of a static identifier and dynamically ~~assigned network~~ address, in ~~a destination communication node (4100), in a~~ the store-and-forward network where host reachability is obtained by association of static identifier and dynamic~~ally assigned network~~ address.

2.   ~~(Amended):~~____Communication model according to Claim 1 ~~above that is~~ characterized in that ~~a~~ the procedure by which the compared elements in the said communication model is known ~~an~~ by the originator communication node ~~(2000 or 5300)~~ is executed in the following sequence:

(1) ~~The~~ the originator communication node ~~(2000 or 5300)~~ performs name query to ~~a~~ the mapping ~~notification~~ announcement system ~~(1000)~~, using ~~a~~ the static identifier of ~~a~~ the destination communication node ~~(4100)~~ as a key~~.~~;

(2) ~~In~~ in response to the name query, the mapping ~~notification~~ announcement system ~~(1000)~~ performs name resolution, returning ~~a dynamically assigned network~~ the dynamic address of the destination communication node ~~(4100)~~;

(3) ~~The~~ the originator communication node ~~(2000 or 5300)~~ sends a sign to the said dynamic~~ally assigned network~~ address, merely requesting the destination communication node ~~(4100)~~ to return a response to the originator communication node ~~(2000 or 5300).~~; and

(4) ~~The~~the destination communication node ~~(4100)~~ sends a countersign to the originator communication node ~~(2000 or 5300)~~, that is, it sends a new carrier signal carrying the reply that should be made.

3.   ~~(Amended):~~ ____Communication model according to Claim 1 ~~above that is~~ characterized in that a signal is used to send information that makes ~~an~~the originator communication node ~~(2000 or 5300) confirm~~check the said host reachability and that is sent from ~~a~~the destination communication node ~~(4100)~~

5   to the originator communication node ~~(2000 or 5300)~~.

4.   ~~(Amended):~~ ____Communication model according to Claim ~~3 above that is~~1 characterized in that ~~the~~a signal is used to send information that makes ~~an~~ the originator communication node ~~(2000 or 5300) confirm~~ check the said host

10   reachability and that is ~~a reply that should be made by a~~sent from the destination communication node ~~(4100) and in that a signal is used to send the said information.~~ to the originator communication node   and,

the information that makes the originator communication node check the said host reachability is the reply that should be made by the destination

15   communication node and in that a signal is used to send the said information.

5.   ~~(Amended):~~ ____Communication model according to Claim ~~3 above that is~~1 characterized in that ~~the~~a signal is used to send information that makes ~~an~~ the originator communication node ~~(2000 or 5300) confirm~~ check the said host

20   reachability and that is sent from the destination communication node   to the originator communication node   and,

the information that makes the originator communication node check reachability is ~~a~~the reply that should be made by ~~a~~the destination communication node ~~(4100)~~and additional information and in that a signal is used to send the said

25   information (former information).

6.   ~~(Amended):~~ ____Carrier signal with the function of carrying information between ~~an~~the originator communication node ~~(2000 or 5300)~~ and ~~a~~the destination communication node ~~(4100)~~ in a store-and-forward network

30   consisting of the originator communication node ~~(2000 or 5300)~~, destination communication node ~~(4100)~~, and ~~a~~mapping ~~notification~~announcement system ~~(1000)~~, and where host reachability is obtained by association of ~~a~~static

identifier and dynamic~~ally assigned network~~ address. Carrier signal carrying a~~the~~ reply that should be made when the destination communication node ~~(4100)~~ responds to the response request from the originator communication node ~~(2000 or 5300)~~.

7. **(Amended)**: Carrier signal according to Claim 6 ~~above that is~~ characterized by carrying additional information in addition to a ~~the~~ reply that should be made.

8. **(Amended)**: ____ Reachability ~~confirmation~~check method by which an~~the~~ originator communication node ~~(2000 or 5300)~~ is made to ~~confirm~~check reachability to a~~the~~ destination communication node ~~(4100)~~ in a store-and-forward network consisting of the originator communication node ~~(2000 or 5300)~~, destination communication node ~~(4100)~~, and a ~~mapping~~ ~~notification~~announcement system ~~(1000)~~, and where host reachability is obtained by association of a ~~static~~ identifier and dynamic~~ally assigned network~~ address. Reachability ~~confirmation~~check method characterized in that arbitrary information is stored at the mapping ~~notification~~announcement system ~~(1000)~~ as the information used when making the originator communication node ~~(2000 or 5300) confirm~~ check reachability to the destination communication node ~~(4100)~~ and in that whether reachability to the destination communication node ~~(4100)~~ is true or false is determined by performing a given communication between the originator communication node ~~(2000 or 5300)~~ and the destination communication node ~~(4100)~~ and then by comparing a ~~the~~ reply that the destination communication node ~~(4100)~~ made to the originator communication node ~~(2000 or 5300)~~ and the said stored arbitrary information.

9. **(Amended)**: ____ Reachability ~~confirmation~~check method according to Claim 8 ~~above that is~~ characterized in that the said arbitrary information is a~~the~~ static identifier at a~~the~~ destination communication node ~~(4100)~~.

10. **(Amended)**: ____ Reachability ~~confirmation~~check method according to Claim 8 ~~above that is~~ characterized in that the said arbitrary information is every

character string replaced with a~the static identifier that an~the originator communication node (2000 or 5300) queries when making a~the communication node discover itself as the destination communication node (4100).

5   11. **(Amended):** Reachability confirmation~check method according to Claim 8 above that is characterized in that the said arbitrary information is the translation rule used by translating a~the static identifier that an~the originator communication node (2000 or 5300) queries when making the communication node discover itself as a~the destination communication node (4100).

10

12. **(Amended):** Reachability confirmation~check method according to Claim 8 above that is characterized in that an~the originator communication node (2000 or 5300) is made to confirm~check that a~the destination communication node (4100) is the true one as follows: arbitrary information is stored at a~the storage

15   device of the destination communication node (4100) as a~the reply that should be made, and then the said stored information is read from the said storage device for communication using a previously agreed method, and then returns a countersign including the said information as a minimum.

20   13. **(Amended):** Reachability confirmation~check method according to Claim 8 above that is characterized in that a mapping notification~announcement system (1000) is selected from among multiple ones (1000) that manage a~the static identifier of a~the destination communication node (4100) and then forward name query is performed to the mapping notification~announcement system

25   (1000), and then the dynamically assigned network address of the destination communication node (4100) is obtained by switching among different mapping notification~announcement systems for each destination communication node (4100) referenced, and then the said given communication is performed to the destination communication node (4100) by using the said obtained dynamically

30   assigned network address.

14. **(Amended):**   Reachability confirmation~check method according to any

~~one of Claims~~ Claim 8 ~~to 13 above that is~~ characterized in that whether reachability to ~~a~~the destination communication node ~~(4100)~~ is true or false is verified by ~~conducting the reachability confirmation method according to any one of Claims 8 to 13 above~~ a mapping announcement system selected from

5   among multiple ones that manage the static identifier of the destination communication node and then forward name query performed to the mapping announcement system , and then the dynamic address of the destination communication node obtained by switching among different mapping announcement systems for each destination communication node referenced,

10   and then the said given communication performed to the destination communication node by using the said obtained dynamic address again after the lapse of a given ~~time~~timer interval when ~~confirmation~~check of reachability to the destination communication node ~~(4100)~~ fails.

15   15. **(Amended):** Reachability ~~confirmation~~check method according ~~to any one of Claims~~Claim 8 ~~to 14 above that is~~ characterized in that ~~an~~the originator communication node ~~(2000 or 5300)~~ conducts the reachability ~~confirmation~~check method in place of a terminal not having the reachability ~~confirmation~~check function.

20

16. **(Amended):** Reachability ~~confirmation~~check method according to ~~any one of Claims~~Claim 8 ~~to 14 above that is~~ characterized in that a further requirement is satisfied that the result of the said reachability ~~confirmation~~check is notified to at least either a given target person or public.

25

17. **(Amended):** Reachability ~~confirmation~~check method according to ~~any one of Claims~~Claim 8 ~~to 16 above that is~~ characterized in that ~~an~~the originator communication node ~~(2000 or 5300)~~ receives a reachability ~~confirmation~~check request for ~~a~~the destination communication node ~~(4100)~~ by a terminal not having

30   the reachability ~~confirmation~~check function, and then the originator communication node ~~(2000 or 5300) confirms~~ checks whether reachability to the destination communication node ~~(4100)~~ is true or false, and then the originator

communication node ~~(2000 or 5300)~~ notifies the result of the ~~confirmation~~check to the said terminal not having the reachability ~~confirmation~~check function.

18.   **(Amended):** ___Reachability ~~confirmation~~check method according to
Claim ~~17 above that is~~ 8 characterized in that ~~when notifying the result of reachability confirmation to~~ the originator communication node   receives a reachability check request for the destination communication node   by a terminal not having the reachability ~~confirmation~~check function, and then the originator communication node   checks whether reachability to the destination communication node   is true or false, and then the originator communication node   notifies the result of the check to the said terminal not having the reachability check function and,
when notifying the result of reachability check to the terminal not having the reachability check function, the time when normal access can be performed is included in the said notification, predicting the time the said terminal is affected by cache.

19.   **(Amended):** ___Reachability ~~confirmation~~check method according to ~~any one of Claims~~ Claim 8 ~~to 14 above that is~~ characterized in that ~~a~~the destination communication node ~~(4100)~~ whose address changes dynamically is managed by ~~confirming~~checking reachability to the destination communication node ~~(4100)~~ before performing network management that uses SNMP, and when the reachability ~~confirm~~check succeeds, the dynamic~~ally assigned network~~ address of the destination communication node ~~(4100)~~ is delivered to network management that uses SNMP.

20.   **(Amended):** ___Reachability ~~confirmation~~check method according to ~~any one of Claims~~Claim 8 ~~to 14 above that is~~ characterized in that when reachability ~~confirmation~~check detects that ~~a~~the destination communication node ~~(4100)~~ is not present, ~~a~~the mapping ~~notification~~announcement system is reconfigured to not ~~notify~~announce the association of static identifier and dynamic~~ally assigned network~~ address of the destination communication node ~~(4100)~~.

6

21. **(Amended):** ___Reachability ~~confirmation~~check method according to Claim ~~20 above that is~~8 characterized in that when reachability ~~confirmation~~check detects that ~~a~~ the destination communication node ~~(4100)~~ is

5   not present, the <u>mapping announcement system is reconfigured to not announce the association of static identifier and dynamic address of the destination communication node and,</u>

the resource record concerning the destination communication node ~~(4100)~~ is deleted at the DNS server that manages the domain name to which the

10   destination communication node ~~(4100)~~ belongs.

22. **(Amended):** Reachability ~~confirmation~~check method according to ~~any one of Claims~~Claim 8 ~~to 14 above that is~~ characterized in that the static identifier indicating ~~an~~the originator communication node ~~(2000 or 5300)~~ is notified to the

15   store-and-forward network.

23. **(Amended):** Reachability ~~confirmation~~check method according to Claim ~~22 above that is~~8 characterized in that closed connection is performed.

20   24. **(Amended):** ___Reachability ~~confirmation~~check method according to ~~any one of~~ Claims 8 ~~to 14 above that is~~ characterized in that the address of ~~a~~the destination communication node ~~(4100)~~ whose reachability ~~confirmation~~check succeeds is stored at ~~an~~ the originator communication node ~~(2000 or 5300)~~ to omit the name resolution process of ~~a~~the mapping ~~notification~~announcement

25   system ~~(1000)~~, and thus to reduce traffic of the mapping ~~notification~~announcement system ~~(1000)~~.

25. **(Amended):** Program product ~~that is~~ characterized in that the result of the reachability ~~confirmation~~check performed using the reachability

30   ~~confirmation~~check method according to ~~any one of Claims~~Claim 8 ~~to 24 above~~ is used as input.

26. **(Amended)**: Program product ~~that is~~ characterized in that the reachability ~~confirmation~~check method according to ~~any one of Claims~~Claim 8 ~~to 24 above~~ is executed by either a computer or network connection equipment.

5   27. **(Amended)**: Media ~~that is~~ characterized in that it can be read by a computer and it stores the program product according to ~~any one of Claims 24 to 25 above~~Claim 8 that the address of the destination communication node whose reachability check succeeds is stored at the originator communication node to omit the name resolution process of the mapping announcement system, and

10   thus to reduce traffic of the mapping announcement system.

28. **(Amended)**: ~~—~~ Communication node that is either a computer or network connection equipment; and that has a means to set at least a sign for each destination communication node ~~(4100)~~, (and to also set ~~a~~ the reply that

15   ought to be made, when the reply is not ~~a~~ the static identifier itself indicating the said destination communication node ~~(4100)~~, and to send the said sign to the said destination communication node ~~(4100)~~; has a means to receive ~~a~~ the countersign returned by the said destination communication node ~~(4100)~~; has a means to compare ~~a~~ the reply that should be made carried by the said received

20   countersign and the said set reply that ought to be made; and that ~~confirms~~checks whether reachability to the destination communication node ~~(4100)~~ is true or false based on whether the result of the comparison is true or false.

25   29. **(Amended)**: Communication node according to Claim 28 ~~above that is~~ characterized in that one mapping ~~notification~~announcement system ~~(1000)~~ is selected from among multiple systems ~~(1000)~~ that manage the static identifier used by ~~a~~ the destination communication node ~~(4100)~~, forward name query is performed, the dynamic~~ally assigned network~~ address of the said destination

30   communication node ~~(4100)~~ is obtained, and the said obtained dynamic~~ally assigned network~~ address is used to communicate to the destination communication node ~~(4100)~~.

30. ~~(Amended):~~ Communication node according to ~~any one of Claims~~Claim 28 ~~to 29 above that is~~ characterized in that when reachability ~~confirmation~~check to ~~a~~the destination communication node ~~(4100)~~ fails, reachability ~~confirmation~~check is performed again after the lapse of a given time interval, to verify whether or not the correct destination communication node ~~(4100)~~ is reached.

31. ~~(Amended):~~ Communication node according to ~~any one of~~ Claims 28 ~~to 30 above that is~~ characterized in that the said reachability is ~~confirmed~~checked in response to a request from a communication node used by a general user.

32. ~~(Amended):~~ Communication node according to ~~any one of Claims~~ Claim 28 ~~to 31 above that is~~ characterized in that the result of the said reachability ~~confirmation~~check is notified to at least either a given target person or the public.

33. ~~(Amended):~~ Communication node according to ~~any one of Claims~~Claim 28 ~~to 32 above that is~~ characterized in that when a reachability ~~confirmation~~check request for ~~a~~the destination communication node ~~(4100)~~ is received from a terminal not having the reachability ~~confirmation~~check function, it is ~~confirmed~~checked whether reachability to the destination communication node ~~(4100)~~ is true or false, and then the result of the reachability ~~confirmation~~check is notified to the said terminal not having the reachability ~~confirmation~~check function.

34. ~~(Amended):~~ ___Communication node according to Claim ~~33 above that is~~ __28__ characterized in that when notifying the result of reachability ~~confirmation~~check to the terminal not having the reachability ~~confirmation~~check function, the time when normal access can be performed is included in the said notification, predicting the time when the said terminal is affected by cache.

35. **(Amended):** ___Communication node according to ~~any one of ClaimsClaim~~ Claim 28 ~~to 32 above that is~~ characterized in that reachability ~~confirmation~~check is connected to the subsequent network management that uses SNMP; in other words, the ~~dynamically assigned network~~ address of ~~a~~the destination communication node ~~(4100)~~ whose reachability is ~~confirmed~~checked is delivered to the said network management, to manage the destination communication node ~~(4100)~~ whose address changes dynamically.

36. **(Amended):** ___Communication node ~~of a~~ (mapping ~~notification~~announcement system ~~(1000) that is)~~ characterized in that when reachability ~~confirmation~~check detects that ~~a~~the destination communication node ~~(4100)~~ is not present on the network, ~~a~~the mapping ~~notification~~announcement system is reconfigured to not ~~notify~~announce the mapped image, or the pair consisting of a static identifier and ~~dynamically assigned network~~ address of the destination communication node ~~(4100)~~.

37. **(Amended):** ___Communication node ~~of a~~ (mapping ~~notification~~announcement system ~~(1000)~~ according to Claim 36 ~~that is~~ characterized in that when reachability ~~confirmation~~check detects that ~~a~~the destination communication node ~~(4100)~~ is not present on the network, the resource record concerning the destination communication node ~~(4100)~~ is deleted at the DNS server that manages the domain name to which the destination communication node ~~(4100)~~ belongs.

38. **(Amended):** ___Communication node according to ~~any one of Claims 28 to 30;~~Claim 28, wherein the communication node receives a countersign carrying the static identifier that indicates ~~an~~the originator communication node ~~(2000 or 5300)~~ in the store-and-forward network.

39. **(Amended):** ___Communication node according to Claim ~~38;~~28, wherein the communication node only provides a given service to the communication node that notifies the static identifier that indicates ~~an~~the originator

communication node (2000 or 5300), to the store-and-forward network set in advance.

40. (Amended): Communication node according to ~~any one of Claims~~ Claim
5 28 ~~to 30~~; wherein the communication node omits the name resolution process of ~~a~~ the mapping ~~notification~~ announcement system (1000) by storing the address of ~~a~~ the destination communication node (4100) whose reachability ~~confirmation~~ check succeeds.

10 41. (Amended): Communication node according to ~~any one of Claims~~ Claim 28 ~~to 40 that is~~ characterized in that its function is shared by multiple devices.

42. (Amended): Program product executed by either a computer or network connection equipment at the communication node according to ~~any one~~
15 ~~of Claims~~ Claim 28 ~~to 40 above~~.

43. (Amended): Media ~~that is~~ characterized in that it can be read by a computer and stores the program product executed by either a computer or network connection equipment according to ~~any one of~~ Claims ~~41 to 42~~
20 ~~above~~ 28.

44. (Amended): Communication node that is either computer or network connection equipment in a store-and-forward network that consists of ~~an~~ the originator communication node (2000 or 5300), destination communication node
25 (4100), and mapping ~~notification~~ announcement system (1000), and where host reachability is obtained by association of a static identifier and ~~dynamically assigned network~~ address; ~~Communication node~~, whose address is assigned dynamically or communication node that is integrated with the said communication node and that is referenced from an external network;
30 ~~Communication node that is~~, characterized in that it is configured in the following manner: arbitrary information used when the originator communication node (2000 or 5300) queries the mapping ~~notification~~ announcement system (1000)

11

about the destination communication node (4100) is stored at the storage device of the said communication node as the reply that should be made, and then the said stored information is read from the said storage device either for a sign or for communication that uses the previously agreed method, and then either a

5   countersign including the said information as a minimum or a response to the communication that uses the previously agreed method.

45. (Amended): ___Communication node according to Claim 44 that is characterized in that the stored reply that should be made is a static identifier

10   used to make the communication node discover itself as the destination communication node (4100).

46. (Amended): ___Communication node according to Claim 44 that is characterized in that it is configured in the following manner: the stored reply

15   that should be made is set as any character string with which a static identifier is replaced that is used when anthe originator communication node (2000 or 5300) queries athe mapping notificationannouncement system (1000) regarding athe destination communication node (4100); and then the said string is stored at the storage device of the said communication node; and then the said stored string

20   is read from the said storage device when a communication request to a given port is received; and then a reply including the said string as a minimum is sent.

47. (Amended): ___Communication node according to Claim 44 that is characterized in that it is configured as follows: the stored reply that should be

25   made is read, and then a string including a string translated based on the translation rule as a minimum is sent as a reply.

48. (Amended): ___Communication node according to Claim 45 that is 44 characterized in that the stored reply that should be made is a static identifier

30   used to make the communication node discover itself as the destination communication node   and,
       it is configured as follows: the host name (FQDN) that is set at athe center-side

mapping ~~notification~~announcement system ~~(1000)~~ updated dynamically by dynamic DNS is set as a readable string read for the said communication node; and then the said string is stored at the storage device of the said communication node; and then the said stored string is read from the said

5   storage device when a communication request to a given port is received; and then a character string including the said string as a minimum is sent as a reply.

49.   **(Amended):** Communication node according to ~~any one of Claims~~Claim 44 ~~to 48 that is~~characterized in that it is configured as follows: in addition to

10   given waiting ports, at least ports for changing the setting of the said communication node or well-known ports for web service for general browsing are provided.

50.   **(Amended):** Communication node according to ~~any one of Claims 42 to~~

15   ~~49 that is~~Claim 44 characterized in that a carrier signal carrying the reply that should be made is sent in response to a sign to allow ~~an~~the originator communication node ~~(2000 or 5300)~~ to ~~confirm~~check reachability to the destination communication node.

20   51.   **(Amended):** ___Program product implemented at either a computer or network connection equipment as a function of the communication node according to ~~any one of Claims~~Claim 44 ~~to 50 above~~.

52.   **(Added):** _____Media ~~that is~~characterized in that it can be read and

25   stores the program product according to Claim ~~51 above.~~44.